



## **ND4000 Series Mobile Ticket Printers**



### ND4000 Mobile Series

### Ticketing Applications

### Models:

- ND4025:** Magnetic stripe tickets
- ND4035:** Contactless Smart tickets

### Applications:

#### **Mobile**

⇒ Mobile sellers can provide tickets on-board trams/trains/buses/metro underground lines or as q-busting sales agents on station platforms, at attractions, leisure and tourism events.

#### **Desktop**

⇒ Small footprint desktop printer ideal for low volume retail point of sale ticket sales

### Options:

#### **Battery Charger**



**Contactless**

**Mag Stripe**

**Lightweight**



- Rail Tickets
- Bus Tickets
- Coach Tickets
- Car Park Tickets
- Event Tickets
- Match Tickets
- Amusement Park Tickets

**Long Life Battery**

**Mobile**

**Compact**

**Reliable**

**Rugged**

**Mobile Ticketing: Enabling customers to buy tickets on the move!**

Mobile Ticketing provides a quick, easy way for organisations to issue tickets with their mobile audience in a convenient environment. Consumers order tickets from the mobile sales agent using their mobile hand held computer or PDA and mobile ticket printer.

### General Specification

	<b>ND4025</b>	<b>ND4035</b>
<b>Model</b>	ND4025	ND4035
<b>Print Technology</b>	Direct Technology	Direct Technology
<b>Resolution</b>	203 dpi	203 dpi
<b>Print/Feed Speeds</b>	150mm / sec	150mm / sec
<b>Media Type</b>	Pre printed or plain ISO sized thermal tickets 54mm x 85-210mm. 0.25 -0.5mm Paper laminates	Pre printed or plain ISO sized thermal tickets 54mm x 85-210mm. 0.25 -0.5mm Paper laminates
<b>Programming Language</b>	Newbury Data programming language available soon	
<b>Encoding</b>	Centre stripe positioning. Low coercivity 75 BPI encoding density. Read/Verify after Write function.	Contactless cards include - Mifare Classic, Mifare Ultralight and more on request. (optional ITSO library)
<b>Ticket/Card Capacity</b>	220 (.25mm)	150 (.5mm)
<b>Standard Interface</b>	Bluetooth	Bluetooth
<b>Case</b>	Plastic	Plastic
<b>Case Colours</b>	Black	Black
<b>Dimensions (mm)</b>	L:300 W:112 H:215	L:300 W:112 H:215
<b>Operating Temperature</b>	+5 to +45 deg C	+5 to +45 deg C
<b>Warranty</b>	12 months parts warranty	12 months parts warranty
<b>Printhead Warranty</b>	6 months or 130,000 tickets	6 months or 130,000 tickets
<b>Applications</b>	Mobile TIS	Mobile TIS

#### Notes:

- 1) All specifications are subject to change without prior notice
- 2) All trademarks acknowledged

Copyright ©Newbury Data Recording Ltd